

Gibraltar Elevator Gear Oil

High Quality Worm Gear Oil

Gibraltar Elevator Gear Oil is a high viscosity, straight mineral-type gear oil for elevator worm gear applications. It's formulated using premium quality, high viscosity index base oil for superior oxidation stability and lasting performance.

Gibraltar Elevator Gear Oil combines superior lubricity properties with inherent load carrying capabilities to ensure premium performance. Specially formulated, **Gibraltar Elevator Gear Oil** is not harmful to yellow metals.

Gibraltar Elevator Gear Oil provides the following benefits:

- Excellent lubricity
- Outstanding oxidation stability
- Safe for brass, copper and other yellow metals
- Natural load-carrying capabilities

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. The information contained herein is subject to change without notice. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation.

DAVID WEBER OIL CO.

601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438. 3178 fax www.weberoil.com

TYPICAL PROPERTIES

PRODUCT DATA SHEET

Industrial Lubricants

| Viscosity, cSt @ 40°C | 795 |
|----------------------------|-------|
| Viscosity, cSt @ 100°C | 53 |
| Viscosity Index | 99 |
| Flash Point, COC, °C, min. | 302 |
| Aniline Point, °C | 128.5 |
| Lbs/Gal | 7.53 |

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. The information contained herein is subject to change without notice. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation.